

EPS SSR-3b
POWER BUS LOSS: RPCM N13B B

ACTION	EQUIP/FUNCTION LOST	CREW INDICATION	NOTES
	RPCM N13B B (Type V)	<u>Caution Messages:</u>	① For IMV valves, use manual override.
	IMV Deck Aft Vlv 1 IMV Deck Fwd Vlv	<u>Advisory Messages:</u> RPCM N13B B Loss Of Comm - NOD1	② Normally the CBMs are powered off. Z1 truss and PMA 3 are attached during 3A using RPCMs N13B and N14B. If RPDA is lost before CBM operations have started, mating will not occur until redundant power sources are provided. If RPDA is lost during CBM operations, mating will continue with N14B.
If CBM controllers are powered by secondary RPCs, continue CBM operations; otherwise, perform CBM MATE MALFUNCTION, all (SODF: OSO)	CBM N1 Nad Pri (1 --- 4) CBM N1 Zen Pri (1 --- 4)	<u>Telemetry:</u> PCS Node 1: EPS <div>Node1: EPS</div>	
On MCC Gα Perform RPCM REMOVE AND REPLACE, all (SODF: OSO).	LT Int NOD1PD2 EmerLtPSN13B4B B	RPCM N13B B - not Active	